

MOBILE STEEL WORK PLATFORM

Features:

- 800 lb. rated capacity
- Grip Strut tread
- Ships all-welded
- 50° Forward descent incline
- Step Lock standard on Handrail models
- 1-1/16" Tubular steel construction
- Two 4" casters for easy transport - Non-Handrail models
- Two 2.5" diameter pads for stability
- Powder coat gray finish
- Complies with applicable OSHA & ANSI standards



WITH HANDRAILS					
GRIP STRUT					
Tri-Arc Model #	# of Steps	Step Width	Platform Height	Overall Height	Overall Length
24"W x 24"L PLATFORM					
WLWP122424SL	2	24"	20"	56"	35"
WLWP132424SL	3	24"	30"	66"	43"
WLWP142424SL	4	24"	40"	76"	51"
WLWP152424SL	5	24"	50"	86"	60"
24"W x 35"L PLATFORM					
WLWP122436SL	2	24"	20"	56"	46"
WLWP132436SL	3	24"	30"	66"	54"
WLWP142436SL	4	24"	40"	76"	62"
WLWP152436SL	5	24"	50"	86"	71"
24"W x 47"L PLATFORM					
WLWP122448SL	2	24"	20"	56"	58"
WLWP132448SL	3	24"	30"	66"	66"
WLWP142448SL	4	24"	40"	76"	74"
WLWP152448SL	5	24"	50"	86"	83"
36"W x 35"L PLATFORM					
WLWP123636SL	2	36"	20"	56"	46"
WLWP133636SL	3	36"	30"	66"	54"
WLWP143636SL	4	36"	40"	76"	62"
WLWP153636SL	5	36"	50"	86"	71"
36"W x 47"L PLATFORM					
WLWP123648SL	2	36"	20"	56"	58"
WLWP133648SL	3	36"	30"	66"	66"
WLWP143648SL	4	36"	40"	76"	74"
WLWP153648SL	5	36"	50"	86"	83"

WITHOUT HANDRAILS					
GRIP STRUT					
Tri-Arc Model #	# of Steps	Step Width	Platform Height	Overall Height	Overall Length
24"W x 24"L PLATFORM					
WLWP022424	2	24"	20"	20"	35"
WLWP032424	3	24"	30"	30"	43"
WLWP042424	4	24"	40"	40"	51"
24"W x 35"L PLATFORM					
WLWP022436	2	24"	20"	20"	46"
WLWP032436	3	24"	30"	30"	54"
WLWP042436	4	24"	40"	40"	62"
24"W x 47"L PLATFORM					
WLWP022448	2	24"	20"	20"	58"
WLWP032448	3	24"	30"	30"	66"
WLWP042448	4	24"	40"	40"	74"
36"W x 35"L PLATFORM					
WLWP023636	2	36"	20"	20"	46"
WLWP033636	3	36"	30"	30"	54"
WLWP043636	4	36"	40"	40"	62"
36"W x 47"L PLATFORM					
WLWP023648	2	36"	20"	20"	58"
WLWP033648	3	36"	30"	30"	66"
WLWP043648	4	36"	40"	40"	74"