

# CANTILEVER LADDERS



## Configurable Solutions for Hard-to-Access Areas

A cantilever ladder provides access above an obstacle or hard to reach area by allowing the platform to cantilever beyond the back of the ladder. Choose from either the Unsupported model which is counterweighted for capacity or the Supported model that has a bottom support legs that can roll under the obstacle. The Cantilever Conversion Kit allows an Unsupported model to be converted to a Supported model by removing the counterweight and adding the bottom extension.

**Platform heights from 50" (5-step) to 90" (9-step)**

**Cantilevered platform is available up to 40" long**

**Counterweighted for a 300 lb. capacity**



### Unsupported Cantilever

### Supported Cantilever

**Same features as the Unsupported Cantilever**

**Support leg rolls under obstructions like tanks, trucks, or machines**

**Allows cantilevered access without added counterweight**



# CANTILEVER LADDERS



Supported 6-step 40" Cantilever



Unsupported 6-step 40" Cantilever

# of Steps	SUPPORTED CANTILEVER		UNSUPPORTED CANTILEVER		Platform Height	Clear Height (to floor)*	Overall Height	Base Width	Base Length
	PERFORATED Tri-Arc Model #	SERRATED Tri-Arc Model #	PERFORATED Tri-Arc Model #	SERRATED Tri-Arc Model #					
<b>20" Cantilever Length</b>									
5	UCS500520246	UCS500520242	UCU500520246	UCU500520242	50"	48"	92"	30"	64"
6	UCS500620246	UCS500620242	UCU500620246	UCU500620242	60"	58"	102"	30"	72"
7	UCS500720246	UCS500720242	UCU500720246	UCU500720242	70"	68"	112"	30"	81"
8	UCS500820246	UCS500820242	UCU500820246	UCU500820242	80"	78"	122"	30"	89"
9	UCS500920246	UCS500920242	UCU500920246	UCU500920242	90"	88"	132"	30"	97"
<b>30" Cantilever Length</b>									
5	UCS500530246	UCS500530242	UCU500530246	UCU500530242	50"	48"	92"	30"	74"
6	UCS500630246	UCS500630242	UCU500630246	UCU500630242	60"	58"	102"	30"	82"
7	UCS500730246	UCS500730242	UCU500730246	UCU500730242	70"	68"	112"	30"	91"
8	UCS500830246	UCS500830242	UCU500830246	UCU500830242	80"	78"	122"	30"	99"
9	UCS500930246	UCS500930242	UCU500930246	UCU500930242	90"	88"	132"	30"	107"
<b>40" Cantilever Length</b>									
5	UCS500540246	UCS500540242	UCU500540246	UCU500540242	50"	48"	92"	30"	84"
6	UCS500640246	UCS500640242	UCU500640246	UCU500640242	60"	58"	102"	30"	92"
7	UCS500740246	UCS500740242	UCU500740246	UCU500740242	70"	68"	112"	30"	101"
8	UCS500840246	UCS500840242	UCU500840246	UCU500840242	80"	78"	122"	30"	109"
9	UCS500940246	UCS500940242	UCU500940246	UCU500940242	90"	88"	132"	30"	117"

## Features:

- 300 lb. rated capacity
- 1"x2" rectangular tube construction
- 24" wide steps and platform
- 50° incline forward descent ladder
- 5"x2" locking casters
- Powder coat yellow finish
- Meets OSHA 1910.29 & ANSI A14.7
- \*Clear Height on Supported Cantilevers is reduced by ~9" tall support

## SUPPORTED CANTILEVER CONVERSION KIT

Converts a **counterweighted Unsupported Cantilever** to a **Supported Cantilever** by adding the base support kit to the base of the ladder and removing and storing the counterweight.

Tri-Arc Model #	Description
<b>UCB2024</b>	20" Extension bottom kit for 20" Cantilever models
<b>UCB3024</b>	30" Extension bottom kit for 30" Cantilever models
<b>UCB4024</b>	40" Extension bottom kit for 30" Cantilever models