

Aluminum Rolling Ladder



- 350 lb. rated capacity
- Solid Ribbed or Grip Strut tread
- Ships all-welded
- 3/4" Sch. 40, 1-1/16" O.D. pipe
- Standard mill finish
- Spring-loaded casters 2 - 7 step models
- Step Lock 8 - 12 step models
- Meets OSHA 1910.29 & ANSI A14.7



Free Safety Training:
WWW.LADDERSAFETYTRAINING.ORG

Model # RIBBED	Model # GRIP STRUT	# of Steps	Step Width	Platform Height	Overall Height	Platform W x L	Base W x D
WITHOUT HANDRAILS							
WLAR002164	WLAR002165	2	16"	20"	20"	16" x 14"	19" x 24"
WLAR002264	WLAR002245	2	24"	20"	20"	24" x 14"	28" x 24"
WLAR003164	WLAR003165	3	16"	30"	30"	16" x 14"	21" x 30"
WLAR003244	WLAR003245	3	24"	30"	30"	24" x 14"	28" x 30"
WLAR004164	WLAR004165	4	16"	40"	40"	16" x 14"	21" x 36"
WLAR004244	WLAR004245	4	24"	40"	40"	24" x 14"	29" x 36"
WITH HANDRAILS							
WLAR102164	WLAR102165	2	16"	20"	50"	16" x 14"	19" x 24"
WLAR102244	WLAR102245	2	24"	20"	50"	24" x 14"	28" x 24"
WLAR103164	WLAR103165	3	16"	30"	60"	16" x 14"	21" x 31"
WLAR103244	WLAR103245	3	24"	30"	60"	24" x 14"	29" x 31"
WLAR104164	WLAR104165	4	16"	40"	70"	16" x 14"	21" x 37"
WLAR104244	WLAR104245	4	24"	40"	70"	24" x 14"	30" x 37"
WLAR105164	WLAR105165	5	16"	50"	80"	16" x 14"	21" x 44"
WLAR105244	WLAR105245	5	24"	50"	80"	24" x 14"	30" x 44"
WLAR106164	WLAR106165	6	16"	60"	90"	16" x 14"	25" x 51"
WLAR106244	WLAR106245	6	24"	60"	90"	24" x 14"	33" x 51"
WLAR107164	WLAR107165	7	16"	70"	100"	16" x 14"	24" x 57"
WLAR107244	WLAR107245	7	24"	70"	100"	24" x 14"	32" x 57"
WLAR108244	WLAR108245	8	24"	80"	110"	24" x 14"	33" x 60"
WLAR109244	WLAR109245	9	24"	90"	120"	24" x 14"	33" x 67"
WLAR110244	WLAR110245	10	24"	100"	130"	24" x 14"	33" x 73"
WLAR111244	WLAR111245	11	24"	110"	140"	24" x 14"	33" x 80"
WLAR112244	WLAR112245	12	24"	120"	156"	24" x 14"	33" x 86"

